

Amendments to the Claims:

This listing will replace all prior versions, and listings, of claims in the application:

1. (currently amended) A process for simultaneously receiving different radio standards, comprising:
 - analog signal processing and subsequently superposing multiple various modulation types of radio standards in a single radio receiver and,
 - carrying out a separation of the multiple various modulation types of radio standards same by [[a]] subsequent digital signal processing.
2. (previously presented) A process according to Claim 1, wherein the superposing is carried out in two frequency ranges.
3. (currently amended) A process according to Claim 1, wherein a ~~the~~ superposing of high frequency signals is carried out prior to a ~~the~~ first mixing step.
4. (previously presented) A process according to Claim 3, wherein the sum of the output of two narrow band oscillators is employed as the local oscillators for the first mixing step.

5. (previously presented) A process according to Claim 3, wherein for each modulation type one filter and amplifier is employed.

6. (previously presented) A process according to Claim 3, wherein for all modulation types a special HF-filter with level accommodation and band selection is employed.

7. (previously presented) A process according to Claim 1, wherein a superposing of a CDMA-encoded and a OFDM-encoded signal is carried out.

8. (previously presented) A process according to Claim 1, wherein prior to decorrelation or demodulation, an A/D conversion is carried out.

9. (previously presented) A process for simultaneously receiving different radio standards, comprising:

- receiving and superposing multiple various modulation types of radio standards, including at least one CDMA encoded signal, in a single radio receiver following an analog signal processing and,
- carrying out a separation of the same by a subsequent digital signal processing.

U.S. Application No.: 09/509,626
AMENDMENT D

ATTORNEY DOCKET: 3926.004

10. (previously presented) A process for simultaneously receiving different radio standards in a single radio receiver, comprising:
- analog signal processing of multiple various modulation types of radio standards in a single radio receiver;
 - superposing said multiple various modulation types of radio standards onto a common intermediate frequency;
 - mixing the product of said superposing; and
 - subsequently carrying out a separation of the mixed product by digital signal processing.